


NOTES:

1. ASPHALT OR ASPHALT MILLINGS PAVING
2. ACCENT PAVING / EDGE RESTRAINT
3. TREE PLANTING SPACED EQUALLY BETWEEN LIGHTING c/w APPROVED GROWING MEDIUM AND VOLUME PER CITY STANDARDS
4. SHARED PATHWAY TO BE BARRIER FREE & UNIVERSAL ACCESSIBILITY STANDARDS
5. 50mm ASPHALT SURFACE. REFER TO BYLAW 7900 FOR STANDARD PAVEMENT STRUCTURE DEPTHS.
6. 19mm MINUS COMPACTED GRANULAR BASE (95% MPD) – REFER TO TRAIL GUIDELINES CHART FOR MAXIMUM SLOPES, MATERIAL DEPTHS AND SPECIFICATIONS
7. 75mm MINUS COMPACTED SUB-BASE (95% MPD) – REFER TO TRAIL GUIDELINES CHART FOR MAXIMUM SLOPES, MATERIAL DEPTHS AND SPECIFICATIONS
8. REMOVE ALL ORGANIC MATERIAL, LARGE STONES AND COMPACT NATIVE SUBGRADE (95% MPD)
9. ALL DIMENSIONS IN MILLIMETRES UNLESS NOTED OTHERWISE

STANDARD DETAIL DRAWING	DATE: JUN 26/23	CLASS 2 TRAIL MAJOR MULTI-USE URBAN	DWG. NO.	 City of Kelowna
	SCALE: NTS		SS-T02	